



Fineline® DXF/DXLF



Features and Benefits

- Narrow-profile, slotted grid system with 1/4" reveal provides streamlined appearance.
- 1/4" slot accommodates partition attachments and pendent-mounted light fixtures.
- Mitered intersections offer a clean, tailored appearance.
- Meets or exceeds all national code requirements, including seismic and fire-rated assemblies up to 1 hour.
- Optional air diffuser provides clean, uninterrupted ceiling plane.
- Accepts CELEBRATION™ metal ceiling panels for ceiling area accents without changing grid system.
- Hot-dipped galvanized steel body inhibits red rust.


Applications

- All interior general use areas
- Fire-rated, interior general use areas



- System meets or exceeds UL load compliance specifications per ASTM C635.

Profile








Fineline® DXF/DXLF

DOWN® Brand Suspension Systems
Narrow 9/16" Face
with 1/4" Reveal


Technical Service 800 USG.4YOU
Web Site www.usg.com
Samples/Literature 888 874.2450
Samples/Literature Fax 888 874.2348
Customer Service 800 950.3839
Literature Number AC3034




UL Classified—Rated Load^{1,2,3}

9/16" Tee System	ASTM Class	Length	Height	Item No. ⁴	Class	Color	4' Hanger Spacing	5' Hanger Spacing	6' Hanger Spacing
	Intermediate Duty	10'	1-25/32"	DXF2924-10	Class A	Flat White Custom	12 lbs./LF	6.6 lbs./LF	3.6 lbs./LF
				DXF2924	Class A	Flat White Custom			
				DXLF2924		Flat White Custom			
	Heavy Duty	12'	1-25/32"	DXFH2924	Class A	Flat White Custom	16 lbs./LF	8.3 lbs./LF	4.9 lbs./LF
		2'	1-25/32"	DXF229	Class A	Flat White Custom			
				DXLF229		Flat White Custom			
		4'	1-25/32"	DXF429	Class A	Flat White Custom			
		4'	1-25/32"	DXF429N ⁸	Class A	Flat White Custom			
				DXLF429N ⁸		Flat White Custom			
		5'	1-25/32"	DXF529N ⁸	Class A	Flat White Custom			

Wall Moldings





Shadowline Wall Angle MS174





Wall Angle M9



Grid/Edge



Wall Molding Detail⁹



Color

Contact your Customer Service representative for color requests.

Material

Double web hot-dipped galvanized steel tee.

Recycled content

25%. For details, see the Recycled Content selector.

Installation

Must be installed in compliance with ASTM C636, CISCA, and standard industry practices.

Limitations

Severe Environmental Requirements: For exposed grids in non-fire-rated, high-humidity applications, use AX™ or ZXL™ painted suspension systems. For exterior applications, suspension should be reviewed by a

structural engineer.

ICBO Evaluation Report Compliance

See ICBO Evaluation Service, Inc., Evaluation Report No. 2244 for allowable values and/or conditions of use concerning material presented in this document, as it is subject to re-examination, revision, and possible cancellation.

L.A. Research Report Compliance

DOWN® Brand suspension systems manufactured by USG Interiors, Inc., have been reviewed and are approved by listing in one or more of the following L.A. Research Report numbers: 22179, 23451, 24095.

ASTM C635 Standard for Load Compliance

This system meets or exceeds UL load compliance specifications per ASTM C635. Main tees will not deflect more than 1/8" over a 48" span (or (L/360) in light duty, intermediate duty or heavy duty categories.

Accessories

Light frames:
1'x4'-LF14; 2'x2'-LF22;
2'x4'-LF24; 30"x30"-LF3030.

Air diffusers:
Request AC272-290.

FINELINE Fire-Rated Assemblies

1-1/2 hr.: G-264
1 hr.: A-202, D-216, P-254

Footnotes

- Hanger wire spacing and locations must be per the UL design.
- Load test data shows uniform load in lbs./LF based on simple span tests in accordance with ASTM C635 deflection limit on L/360.
- For detailing and module loading request AC3003QRC.
- Some products are available in metric. Call Customer Service for details.
- Standard main tee is notched 24" o.c. but has cross tee holes 12" o.c.

6. Cross tee hole spacings available for 24", 30", and 48" modules except DXLF.

7. Cross tees also available in 1' and 30" lengths.

8. N = Notch at midpoint.

9. For more information about moldings, see Perimeter Options selector.

10. Panels must be field-cut to size at the perimeter.

SAFETY FIRST!

Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.



Manufactured by
USG Interiors, Inc.
125 South Franklin Street
Chicago, IL 60606

The following are trademarks of USG Interiors, Inc., or a related company:
AX, CELEBRATION, CUMAPLUS, DOWN, ECLIPSE, FINELINE, QUICK-RELEASE, USG, ZXL.

AC3034/rev. 6-04
© 2004, USG Interiors, Inc.
Printed in U.S.A.