



PANZ Metal Ceiling Panels (FL edge) in Flat White/
DONN CENTRICITEE DXT Suspension System

LEED Credits

Recycled Content: Up to 90%

MR				EQ		
Waste Reduction	Recycled Content	Regional Materials ¹	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance ²
●	●	●				●

Features and Benefits

- Simple lay-in design provides 100% access
- ACOUSTIBOND® sound backer produces .65 NRC without additional acoustical material when panels are installed within an enclosed plenum (minimum plenum depth: 18")
- Available in numerous perforation patterns (see pages 42-47)
- Creates reveal edge on field-cut panel
- Available with same edge details as USG acoustical panels

Applications


- Computer and utility rooms
- Entertainment
- Gaming
- Frequently accessed plenums




To order samples, go to usg.com

See IC415 for color and perforation availability.

Diamondflex²



Louvered Bright White Louvered Bright Silver




Sheer Bright White Sheer Bright Silver

Painted Metals (HRC Finishes)



Flat White Silver Satin 002 Metallic Copper 1690 Metallic Gold 1691 Metallic Oyster 1652

Premium Metals




Aged Copper 1017 Etched Ice Dark 1016 Etched Ice Light 1015

Wood Tones (HRC Finishes)













Cherry Maple Oak

Anodized Metals



Brushed Aluminum PIA12 Polished Aluminum PM61 Polished Brass PM21 Satin Chrome PM614

	Product Information			
	Materials	Available Sizes	Finishes	
	Panels: Aluminum	2' x 2', 2' x 4', 4' x 4'	2' x 2' panels available with perforation and/or embossing. (see pages 42-47 for other perforation options)	
Acoustics	Description	Optional Acoustical Material	Sound Rating – NRC	
			Perforation A062	Perforation A116
	Perforated panel	ACOUSTIBOND backer ¹	.65	.70
	Perforated panel	1-1/2", 6 lb. density fiberglass (by others)	.90	.95
	Perforated panel	2", .75 lb. fiberglass in poly bag (by others)	.85	.90
Panels	Smooth Panel	Perforated Panel	Perforated Panel with ACOUSTIBOND³ Backer	
				
Edge Details	Square Edge with 15/16" DX[®]/DXL[™] Suspension	Square Edge with 9/16" CENTRICITEE[™] DXT Suspension	Shadowline Edge with 15/16" DX/DXL Suspension	Fineline Edge with 9/16" CENTRICITEE DXT Suspension
				
	Fineline Edge with 9/16" FINELINE[®] DXF Suspension	Fineline Edge with 9/16" FINELINE[®] 1/8 DXFF Suspension		
				
	 High Recycled Content Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.			

For More Information

Product literature
 System brochure: IC415
 Data sheet: IC314

Online tools
usgdesignstudio.com

Light reflectance
 Flat White: LR-0.8
 (less with perforations).

Recycled content
 Panz aluminum panels: up to 90% recycled content.

Footnote

1. For details, see LEED report generator at usgdesignstudio.com.
2. Requires perforation and ACOUSTIBOND backer.
3. ACOUSTIBOND backer not standard with DIAMONDFLEX panels.