

10

Year Availability  
707, 708, 711

HRC

High Recycled Content



GLACIER Panels/  
DOWN FINELINE DXFF Suspension System

### LEED Credits

Recycled Content: 70% – 71%

MR				EQ		
Waste Reduction <sup>1</sup>	Recycled Content	Regional Materials <sup>2</sup>	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●	●	●	●	●

### Features and Benefits

- Heavily textured cast product with durable surface that resists scrapes commonly caused by accessing the ceiling plenum
- Combine 12"x12" tile with the DOWN® brand DX®/DXL™ concealed suspension system to create a monolithic ceiling surface
- Integral color masks nicks and scratches and enhances lifelong panel appearance
- Optional FIRECODE™ formulation designed to meet life safety codes

### Applications

- Food courts
- Hospitality
- Libraries
- Restaurants

### Substrate

- Cast mineral fiber



Heavy-textured panel

### To order samples, go to usg.com

See individual items for color availability.

**Standard Colors**

White	Parchment 103	Manila 246	Beige 142	Straw 143	Sandstone 090	Taupe 107
Charcoal 534	Flat Black 205	Silvertone 052	Mist 053			

**Advantage Colors**

Breeze 2659	Blue Grey 564	Azure 2660	Slate 568	Spruce 567	Tuscany 2663	Sorbet 2658
Squash 2661	Safari 2662	Redwood 566	Sienna 565	Halo 206	Nectar 546	Quartz 082

UL Classified													
Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR <sup>3</sup>	Color <sup>4</sup>	Grid Options	VOC <sup>5</sup> Emissions	Abuse-Resistant	Recycled Content <sup>2</sup>	Panel Cost	
GLACIER Panels	SL 	2'x2'x3/4" Foil-Back	Class A	<b>707</b>	.65	35	.70	White Standard Advantage	A	Zero		71% 	\$\$
		2'x2'x3/4" Foil-Back		<b>715</b>	.65	35	.70	White	A	Zero		70% 	\$\$
		2'x4'x3/4" Foil-Back	Class A	<b>711</b>	.65	35	.70	White	A	Zero		71% 	\$\$
	FL 	2'x2'x3/4" Foil-Back	Class A	<b>708</b>	.65	35	.70	White Standard Advantage	B, C, D, F	Zero		71% 	\$\$
GLACIER Tile <sup>5,6,7</sup>	SESK 	12"x12"x3/4"	Class A	<b>701</b>	.65	25	.70	White	E	Zero		71% 	\$\$\$\$

**Legend**

**Zero Emissions (VOC Class)**

Classified as zero-emitting per standards established by the Collaborative for High-Performance Schools (CHPS), following California Specification 01350 testing methods.

**High Recycled Content**

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

	A DX®/DXL™	B CENTRICITEE™ DXT	C FINELINE® DXF	D FINELINE® 1/8 DXFF	E DX®/DXL™ Concealed	F IDENTITEE™ DXI™
<b>Grid Profile Options</b>						

**Physical Data/  
Footnotes**

**Product literature**  
Data sheet: SC1819

**ASTM E1264 classification**  
Type III, Form 4, Pattern F

**ASTM E84 surface burning characteristics**

Class A  
Flame spread: 25  
Smoke developed: 50

**Weight**  
1.45 lb./sq. ft. (Class A panels and tile)  
1.50 lb./sq. ft. (FIRECODE panel)

**Thermal resistance**  
R-1.7 (Class A)  
R-1.3 (FIRECODE)

**Maximum backloading**  
See Warranty for details.

**Maintenance**  
Can be cleaned easily with a soft brush or vacuum.

**Texture**  
The manufacturing process for cast ceiling panels creates natural, subtle texture variations, which is a distinguishing feature of these products. Because of potential variances between production dates, we recommend ordering and installing cast products by production lot number.

**Footnotes**

1. Applies when USG acoustical ceilings recycling program is utilized.
2. For details, see LEED report generator at usgdesignstudio.com.
3. LR values are shown as averages.
4. See Colors selector for more information.
5. Texture appearance will vary based on ceiling height, installation methods, and natural variation of the product.
6. Contact USG for adhesive recommendation for 12" x 12" glue-up applications.
7. Not UL Classified for acoustics.

8. No formaldehyde is added to any ingredient or during the manufacturing process for all mineral fiber acoustical ceiling products manufactured by USG Interiors, Inc.