

10

Year Availability  
808,809

HRC

High Recycled Content



SANDRIFIT Panels with *CLIMAPlus* Superior Performance/  
DONN DX/DXL Suspension System

### LEED Credits

Recycled Content: 70% – 71%  
*CLIMAPlus* Superior Performance for Mold and Mildew

MR				EQ		
Waste Reduction <sup>1</sup>	Recycled Content	Regional Materials <sup>2</sup>	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●	●	●	●	●

### Features and Benefits

- Uniquely textured cast product with durable surface that resists scrapes commonly caused by accessing the ceiling plenum
- Integral color masks nicks and scratches.
- Optional FIRECODE™ formulation designed to meet life safety codes
- *CLIMAPlus* 30-year lifetime system warranty to withstand conditions up to 104 °F (40 °C)/95% relative humidity without visible sag when used with a DONN® brand suspension system

### Applications

- Conference and lobby areas
- Department stores
- Entertainment and gaming
- Executive offices
- Restaurants

### Substrate

- Cast mineral fiber



Fine-textured panel

To order samples, go to [usg.com](http://usg.com)

**Standard Colors**

White	Parchment 103	Manila 246	Beige 142	Straw 143	Sandstone 090	Taupe 107
Charcoal 534	Flat Black 205	Silvertone 052	Mist 053			

**Advantage Colors**

Breeze 2659	Blue Grey 564	Azure 2660	Slate 568	Spruce 567	Tuscany 2663	Sorbet 2658
Squash 2661	Safari 2662	Redwood 566	Sienna 565	Halo 206	Nectar 546	Quartz 082

30

Year System Warranty  
 – No visible sag  
 – Mold/mildew protection

SANDRIFT  
*CLIMAPLUS*  
 Panels

SANDRIFT  
 Non-*CLIMAPLUS*  
 Panels

UL Classified													
Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR <sup>3</sup>	Color <sup>4</sup>	Grid Options	VOC <sup>5</sup> Emissions	Anti-Mold & Mildew	Abuse Resistant	Recycled Content <sup>2</sup>	Panel Cost
SL 	2'x2'x3/4" Paper-Back	Class A	808	.70 	38	.83	White Standard Advantage	A	Zero			71% 	\$\$
FL 	2'x2'x3/4" Paper-Back	Class A	809	.70 	38	.83	White Standard Advantage	B, C, D, E	Zero			71% 	\$\$
SL 	2'x2'x3/4" Foil-Back		815	.55 	35	.83	White	A	Zero			70% 	\$\$

**Legend**

Zero Emissions (VOC Class)

Classified as zero-emitting per standards established by the Collaborative for High-Performance Schools (CHPS), following California Specification 01350 testing methods.

CLIMAPLUS Superior Performance<sup>5</sup>

Contains a broad-spectrum antimicrobial treatment on the face and back of the panel that provides guaranteed resistance against the growth of mold and mildew.

High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

A DOW® DX®/DXL™	B CENTRICITEE™ DXT	C FINELINE® 1/8 DXFF	D FINELINE DXF	E IDENTITEE™ DXI™

**Grid Profile Options**

**Physical Data/ Footnotes**

**Product literature**  
 Data sheet: SC1841

**ASTM E1264 classification**  
 Type III, Form 4, Pattern Z

**ASTM E84 surface burning characteristics**  
 Class A  
 Flame spread: 25  
 Smoke developed: 50

**Weight**  
 1.65-1.70 lb./sq. ft. (Class A)  
 FIRECODE weight

**Thermal resistance**  
 R-1.7 (Class A)  
 R-1.3 (Firecode)

**Maximum backloading**  
 See Warranty for details.

**Maintenance**  
 Can be cleaned easily with a soft brush or vacuum.

**Texture**  
 The manufacturing process for cast ceiling panels creates natural, subtle texture variations, which is a distinguishing feature of these products. Because of potential variances between production dates, we recommend ordering and installing cast products by production lot number.

**Footnotes**

1. Applies when USG acoustical ceilings recycling program is utilized.
2. For details, see LEED report generator at usgdesignstudio.com.
3. LR values are shown as averages.
4. To highlight the unique texture of SANDRIFT CLIMAPLUS panels, choose light colors. See Colors selector for more information.
5. Panel face and back surfaces treated with a patented, broad-spectrum antimicrobial standard formulation that inhibits and retards the growth of mold and mildew. For details, see *Ceiling Systems*

**Warranties and Limitations** (SC2102) and *CLIMAPLUS Ceilings Certification of Performance* (SC2451).

6. No formaldehyde is added to any ingredient or during the manufacturing process for all mineral fiber acoustical ceiling products manufactured by USG Interiors, Inc.

